

MODEL TS 5900

TECHNICAL SPECIFICATION

LOA	5.9M
BEAM	2.3M
DRAFT	0.45M
HULL WEIGHT	850 kg
PERSONS	8
MAX ENGINE	115 HP
REC. ENGINE	FROM 70HP
MAX LOAD	1000KG
TRANSOM	UL TYPE
DEADRICE	22 degree
FUEL TANK	130 L



Standard scope of supply:

- | | |
|--|---|
| 1 Hull Material HDPE (black colour) | 22 Hatch holder stainless steel - 3 pcs |
| 2 Fender 10 mm HDPE (red colour UV resistance) | 23 Storage compartment + door in front - 1pcs |
| 3 Foam filling inside of the 500mm tube | 24 Technical storage in AFT with hatches - 2 pcs |
| 4 Compartments in tube structure splitted by bulkheads | 25 Steps in AFT with anti slip cnc method – 2 pcs |
| 5 Self-drainage deck – 2 outlets D 50mm in transom | 26 Step platform with anti slip cnc methhod – 1pcs |
| 6 Drainage plug in transom D25 mm from DB | 27 Seats place on boards L 2000x 230 mm - 2pcs |
| 7 Tunnel in the DB for laying control systems D75mm– 2 pcs | 28 Soft seats on Aft storage compartment t=50 mm - 3 pcs |
| 8 Towing points in AFT – 2pcs | 29 Non-slip rubber mat on the deck (removable) |
| 9 Inspection hatch D 190mm for Fuel tank -1 pcs | 30 Center Console + Access Hatch - 1pcs |
| 10 Inspection hatch D 190mm for engine bolts installation - 1pcs | 31 Windshield for console with SS railing - 1pcs |
| 11 Drainage plugs d 25 mm in technical compartmets - 2 pcs | 32 Main switch installed to Center console (Blueseas) -1 pcs |
| 12 Drainage plug d 25 mm from Fuel compartment - 1 pcs | 33 Switch panel for nav. lights + reserve (total 4 pcs Bluesea) |
| 13 Fuel tank 130 L installed in DB -1 pcs | 34 Battery holder under the console x 2 pcs |
| 14 Fuel inlet D 50 mm in aft - 1 pcs | 35 Manual Bilge pump from DB (35L per min) |
| 15 Fuel tank ventilation system | 36 Safety rope around boat D18 mm (Navyblue) |
| 16 Fuel compartment ventilation system | 37 A-frame in AFT for navigation light,etc (Stainless steel) |
| 17 Reinforced transom by AL angle bar 130x65 | 38 Bow railings (Stainless steel) |
| 18 Mooring places (Ducks) – 4 pcs | 39 Top light |
| 19 Lifting pad eyes – 4 pcs | 40 Fuel separator outside box |
| 20 Storage compartment in AFT - 3pcs | 41 Ultraflex Hose Through Bulkhead for hydraulic steering |
| 21 Lockers for storage hatch (Roca) - 6pcs | 42 CE certification, category C |