

MODEL TS 7990

TECHNICAL SPECIFICATION

LOA	7.99 M
BEAM	2.5M
DRAFT	0.45M
HULL WEIGHT	1400 kg
PERSONS	12
MAX ENGINE	350 HP
REC. ENGINE	FROM 200HP
MAX LOAD	1600KG
TRANSOM	UL TYPE
DEADRICE	22 degree
FUEL TANK	210 L



Standard scope of supply:

- 1 Hull Material HDPE (black colour)
- 2 Fender 10 mm HDPE (red colour UV resistance)
- 3 Foam filling inside of the 500mm tube
- 4 Compartments in tube structure splitted by bulkheads
- 5 Self-drainage deck – 2 outlets D 63 mm in transom
- 6 Drainage plug in transom D25 mm from DB
- 7 Tunnel in the DB for laying control systems D 90mm– 2 pcs
- 8 Towing points in AFT – 2pcs
- 9 Inspection hatch D 190mm for Fuel tank -1 pcs
- 10 Inspection hatch D 190mm for engine bolts installation - 1pcs
- 11 Drainage plugs d 25 mm in technical compartemts - 2 pcs
- 12 Drainage plug d 25 mm from Fuel compartment - 1 pcs
- 13 Fuel tank 210 L installed in DB -1 pcs
- 14 Fuel inlet D 50 mm in aft - 1 pcs
- 15 Fuel tank ventilation system
- 16 Fuel compartment ventilation system
- 17 Reinforced transom by AL angle bar 130x65
- 18 Mooring places (Ducks) – 4 pcs
- 19 Lifting pad eyes – 4 pcs
- 20 Storage compartment in AFT - 3pcs
- 21 Lockers for storage hatch (Roca) - 6pcs
- 22 Hatch holder stainless steel - 3 pcs
- 23 Storage compartment + door in front - 1pcs
- 24 Technical storage in AFT with hatches - 2 pcs
- 25 Steps in AFT with anti slip cnc method – 2 pcs
- 26 Step platform with anti slip cnc method – 1pcs
- 27 Soft seats on Aft storage compartment t=50 mm - 3 pcs
- 28 Non-slip rubber mat on the deck (removable)
- 29 Center Console + Access Hatch - 1pcs
- 30 Main switch installed to Center console (Blueseas) -1 pcs
- 31 Switch panel for nav. lights + reserve (total 4 pcs Bluesea)
- 32 Battery holder under the console x 2 pcs
- 33 Manual Bilge pump from DB (35L per min)
- 34 Safety rope around boat D18 mm (Navyblue)
- 35 A-frame in AFT for navigation light,etc (Stainless steel)
- 36 Bow railings (Stainless steel)
- 37 Navigation lightsights
- 38 Top light
- 39 Fuel separator outside box
- 40 Ultraflex Hose Through Bulkhead for hydraulic steering
- 41 CE certification, category C