

MODEL TS 8200

TECHNICAL SPECIFICATION

LOA	8.2M
BEAM	2.5M
DRAFT	0.45M
HULL WEIGHT	1540 kg
PERSONS	12
MAX ENGINE	300 HP
REC. ENGINE	FROM 200HP
MAX LOAD	1800KG
TRANSOM	UL TYPE
DEADRICE	22 degree
FUEL TANK	210 L



Standard scope of supply:

- | | |
|--|--|
| 1 Hull Material HDPE (black colour) | 23 Storage compartment + door in front - 1pcs |
| 2 Fender 10 mm HDPE (red colour UV resistance) | 24 Technical storage in AFT with hatches - 2 pcs |
| 3 Foam filling inside of the 500mm tube | 25 Steps in AFT with anti slip cnc method – 2 pcs |
| 4 Compartments in tube structure splitted by bulkheads | 26 Step platform with anti slip cnc method – 1pcs |
| 5 Self-drainage deck – 2 outlets D 50mm in transom | 27 Seats place on boards L 2000x 230 mm - 2pcs |
| 6 Drainage plug in transom D25 mm from DB | 28 Soft seats on Aft storage compartment t=50 mm - 3 pcs |
| 7 Tunnel in the DB for laying control systems D90mm– 2 pcs | 29 Non-slip rubber mat on the deck (removable) |
| 8 Towing points in AFT – 2pcs | 30 Center Console + Access Hatch - 1pcs |
| 9 Inspection hatch D 190mm for Fuel tank -1 pcs | 31 Windshield for console with SS railing - 1pcs |
| 10 Inspection hatch D 190mm for engine bolts installation - 1pcs | 32 Main switch installed to Center console (Blueseas) -1 pcs |
| 11 Drainage plugs d 25 mm in technical compartments - 2 pcs | 33 Switch panel for nav. lights + reserve (total 4 pcs Blueseas) |
| 12 Drainage plug d 25 mm from Fuel compartment - 1 pcs | 34 Battery holder under the console x 2 pcs |
| 13 Fuel tank 210 L installed in DB -1 pcs | 35 Manual Bilge pump from DB (35L per min) |
| 14 Fuel inlet D 50 mm in aft - 1 pcs | 36 Safety rope around boat D18 mm (Navyblue) |
| 15 Fuel tank ventilation system | 37 A-frame in AFT for navigation light,etc (Stainless steel) |
| 16 Fuel compartment ventilation system | 38 Bow railings (Stainless steel) |
| 17 Reinforced transom by AL angle bar 130x65 | 39 Navigation lightsight |
| 18 Mooring places (Ducks) – 4 pcs | 40 Top light |
| 19 Lifting pad eyes – 4 pcs | 41 Fuel separator outside box |
| 20 Storage compartment in AFT - 3pcs | 42 Ultraflex Hose Through Bulkhead for hydraulic steering |
| 21 Lockers for storage hatch (Roca) - 6pcs | 43 CE certification, category C |
| 22 Hatch holder stainless steel - 3 pcs | |